Engine Covers

Automotive | Drivetrain | Transmission

Print Date: 2023-03-02

Benefits

- Reliable
- High heat resistant
- Great surface appearance
- · Low warpage levels
- Cost effective
- · High flowability enables thin wall designs



Details

Akulon® PA6 is a thermoplastic with high heat resistant properties making it an ideal choice for applications such as engine covers due to its high temperature resistance, great surface appearance, and low warpage levels. Akulon® Ultraflow grades allow more cost effectiveness with a 25% cycle time advantage and high flowability that enables thinner wall designs.

Products

Akulon® Ultraflow K-FHGM22 PA6-(GF+MD)30 Akulon® Ultraflow K220-HGM44 PA6-(GF+MD)40 Akulon® K223-HGM24 PA6-(GF+MD)30

Akulon® K224-HGM35 PA6-(GF+MD)40





Akulon®, Arnite®, Arnitel®, EcoPaXX®, ForTii®, Novamid®, Stanyl®, UDea™ and Xytron™ are trademarks of DSM.

Seller represents and warrants exclusively that on the date of delivery by Seller the product shall be in conformity with the specifications agreed upon. Seller makes no other representations or warranties, whether express or implied

Seller is not responsible or liable for the design of the products of the Customer and it is the responsibility of the Customer to determine that the Seller's product is safe, complies with application laws and regulations, and is technically or otherwise fit for its intended use. Seller does not endorse or claim suitability of its products for a specific application and disclaims each and every representation or warranty, whether express or implied, in that respect.

Typical values are indicative only and are not to be construed as being binding specifications. Colorants in the product or other additives may cause significant variations in typical values. This document replaces all previous versions relating to this subject.



