

Gradeslate for industrial and consumer applications

Energy lives here™

Family	Grade series*	Description	Hardness reference	UL listed	Key attributes**
General purpose	101-xx/103-xx 201-xx/203-xx 111-xx 211-45	Black Natural Black Natural	55A – 50D 55A – 50D 35A, 45A 45A	✓ ✓ ✓ ✓	<ul style="list-style-type: none"> Basic molding and extrusion Hard grades (>85A) ideal for blow molding Highest level of elastomeric properties (i.e., lowest compression/tension set)
	8201-xx	Natural	60A – 90A	✓	<ul style="list-style-type: none"> Basic molding and extrusion Hard grade (90A) ideal for blow molding Excellent colorability
Specialty molding	121-xxM100	Black	50A – 85A	✓	<ul style="list-style-type: none"> Outstanding processability for specialty molding Designed for improved UV resistance
	8211-xx	Natural	35A – 75A	✓	<ul style="list-style-type: none"> Outstanding processability for specialty molding Excellent colorability
Extrusion	121-xxW175 121-73W175 691-xxW175	Black Black Natural	58A – 50D 73A 65A, 73A	✓ ✓	<ul style="list-style-type: none"> Designed and released against specific extrusion performance criteria 121 series designed for improved UV resistance
	251-xxW232	Natural	70A – 92A	✓	<ul style="list-style-type: none"> UL 94 V-0 rated except 85A is V-2 rated
Flame retardant	151-xxW256	Black	70A	✓	<ul style="list-style-type: none"> UL 94 5VA rated UV resistant (UL (f1) rated) Stabilized against copper and other metal-catalyzed degradation
Detergent resistant	101-xxW255 201-55W255	Black Natural	45A, 55A 55A	✓	<ul style="list-style-type: none"> Property retention in presence of typical dishwasher and washing machine detergents Stabilized for protection against copper and other metal-catalyzed degradation
	101-60W261	Black	60A	✓	<ul style="list-style-type: none"> Very good physical properties with excellent flexural crack and chemical resistance
Potable water	241-xx 241-xxW236	Natural Natural	55A, 64A 73A, 80A	✓	<ul style="list-style-type: none"> NSF 61 certified (241-xx also NSF 51 certified) W236 grades stabilized against copper and other metal-catalyzed degradation
Non-fatty food contact	271-xx/273-xx 8271-xx	Natural Natural	55A – 40D 55A – 75A	✓ ✓	<ul style="list-style-type: none"> FDA non-fatty food contact rating NSF 51 certified 8271-XX non-hygroscopic; enhanced colorability
	121-xxB260	Black	40A – 70A – 80A		<ul style="list-style-type: none"> Improved bonding to TPV, EPDM and PP Low CoF to reduce friction
Bonding	291-60B150 291-75B150 8191-55B100 8211-55B100	Natural Natural Black Natural	60A 75A 55A 55A	✓ ✓ ✓ ✓	<ul style="list-style-type: none"> Insert or 2 shot molding Bonds to PC, ABS, PS and other engineering thermoplastics (ETPs) B100 grades also bond to PP
	8291-85TL	Natural	85A		<ul style="list-style-type: none"> Extrusion Bonds to metal and PP
	121-xx/123-xx 121-80 8221-xx	Black Black Natural	80A – 40D 80A 60A, 70A	✓ ✓	<ul style="list-style-type: none"> Designed for UV resistance UL listed grades are UL (f1) rated
	Feedstock	RC8001	Natural	55A	

* xx = hardness reference value

** Comparisons are made to the grades in the first section of the general purpose family below

Bonding grades – licensed technology

Bonding products based on Santoprene™ TPV are available from RTP Company.

See www.rtpcompany.com for more information.

RTP Company grade designation*	Hardness reference	Features	Corresponding discontinued Santoprene TPV grade*
RTP 6091-xx BLK	55A - 85A	Bonds to nylon 6, nylon 6 (30% glass filled), nylon 6,6 and PP	191-xxPA
RTP 6091-xx NAT	55A - 85A		8291-xxPA
RTP 6091 B-60A BLK	60A	Bonds to nylon 6, nylon 6 (30% glass filled), nylon 6,6 and nylon 12	8191-60B500
RTP 6091 B-60A NAT	60A		8291-60B500
RTP 6091 B-85PA12 BLK	85PA12	Bonds to nylon 12, nylon 6, nylon 6 (30% glass filled), nylon 6,6 and PP	191-85PA12

*xx = hardness reference value

Santoprene thermoplastic vulcanizates (TPVs) have a successful track record for flexible, high-quality engineered parts used in a wide range of industrial and consumer applications. Combining the characteristics of vulcanized rubber with the processing ease of thermoplastics, Santoprene TPVs deliver excellent long-term performance, the potential for reduced system costs, and the possibility of sustainability benefits.

Excellent performance

- Long-term durable sealing capabilities in harsh environments
- Outstanding physical properties
- High-end finished part aesthetics through aspect harmonization and excellent surface qualities

Reduced part/system costs

- Ease of processing which allows a broad processing window, fast cycle times and tight tolerances in part design
- Design flexibility which allows the combination of hard/soft materials
- Lower scrap rates compared to thermoset rubber materials

Sustainability opportunities

- The lower density of Santoprene TPVs compared to thermoset rubber and other thermoplastic elastomers can contribute to reduced part weight
- Reduction in overall waste in the manufacturing process as scrap produced during processing can be recycled
- Due to integrated manufacturing, such as multi-shot injection molding, chemical usage is reduced because spray coatings and adhesive application are not needed
- Reduced manufacturing energy consumption as heat curing is not required compared to EPDM thermoset rubber
- Less manufacturing space because typical TPV extrusion lines only need one-third of the space used by comparable EPDM thermoset lines

©2014 ExxonMobil. ExxonMobil, the ExxonMobil logo, the interlocking "X" device and other product or service names used herein are trademarks of ExxonMobil, unless indicated otherwise. This document may not be distributed, displayed, copied or altered without ExxonMobil's prior written authorization. To the extent ExxonMobil authorizes distributing, displaying and/or copying of this document, the user may do so only if the document is unaltered and complete, including all of its headers, footers, disclaimers and other information. You may not copy this document to or reproduce it in whole or in part on a website. ExxonMobil does not guarantee the typical (or other) values. Any data included herein is based upon analysis of representative samples and not the actual product shipped. The information in this document relates only to the named product or materials when not in combination with any other product or materials. We based the information on data believed to be reliable on the date compiled, but we do not represent, warrant, or otherwise guarantee, expressly or impliedly, the merchantability, fitness for a particular purpose, freedom from patent infringement, suitability, accuracy, reliability, or completeness of this information or the products, materials or processes described. The user is solely responsible for all determinations regarding any use of material or product and any process in its territories of interest. We expressly disclaim liability for any loss, damage or injury directly or indirectly suffered or incurred as a result of or related to anyone using or relying on any of the information in this document. This document is not an endorsement of any non-ExxonMobil product or process, and we expressly disclaim any contrary implication. The terms "we," "our," "ExxonMobil Chemical" and "ExxonMobil" are each used for convenience, and may include any one or more of ExxonMobil Chemical Company, ExxonMobil Corporation, or any affiliate either directly or indirectly stewarded.

Contact your ExxonMobil Chemical representative for more information:
santoprene.com

S0418-143E49

ExxonMobil
 Energy lives here™