

LNP™ ELCRES™ CRX COPOLYMER RESINS

IMPROVED CHEMICAL RESISTANCE MATERIALS FOR MEDICAL ENCLOSURES AND HOUSINGS

With patient safety at the forefront, the healthcare industry is mobilizing to address the concerns of increasing patient infections associated with medical care, known as hospital-acquired infections (HAIs). To help meet this challenge, medical equipment and high touch surfaces in patient care settings are repeatedly wiped down with increasingly aggressive chemical disinfectants.



NEED FOR IMPROVED CHEMICAL RESISTANCE

Manufacturers of medical equipment for patient monitoring, imaging, diagnostic, fluid and medication delivery need materials that offer improved chemical resistance to the more aggressive disinfectants used today in healthcare settings.

NEW SOLUTION OFFERING

SABIC’s LNP ELCRES CRX resins leverage unique copolymer technology to provide improved chemical resistance for healthcare devices and equipment, compared to existing materials used such as PC/ABS, PC/PBT, or co-polyester resins and blends.

CHEMICAL RESISTANCE DATA – ENVIRONMENTAL STRESS CRACKING (ESC) PERFORMANCE

Compared to traditional PC, ABS, PBT and co-polyester resins and blends — which are potentially incompatible with highly aggressive disinfectants such as quaternary ammonium compounds — the new LNP ELCRES CRX resins can help prevent stress cracking and mitigate crack propagation.

PLASTICS DETERMINATION OF RESISTANCE TO ENVIRONMENTAL STRESS CRACKING (ESC) METHOD

PRODUCT	Mold shrinkage (%)	Exposure days	SANI-CLOTH® Bleach		SANI-CLOTH® HB		SANI-CLOTH® AF3		SANI-CLOTH® plus		Diversey Oxivir® TB		Trichlorosynuric Acid		Cavicide® CavWipes1		SANI-CLOTH® prime		Virex® II256		Virex® TB		CIDEX® OPA Solution		Betadine		IPA (70%)		Ethanol	
			σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b	σ _y	E _b		
PC/ABS	0.6	7	●●	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	■	
PC/PBT	1.0	7	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●		
CRX5421 RESIN	1.5	7	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●		
CRX1414 RESIN	0.8	7	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●		
CRX9411 RESIN	0.8	3	-	-	●●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●●	■	-	-	-	-	-		
	0.8	7	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●	●●		
	0.8	3	-	-	●●	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	●●	●●	-	-	-	-			

SABIC’s ESC method evaluates retention of tensile properties vs. control for up to 7 days.

Compatibility Criteria Color rating	Tensile stress at Yield retention, σ _y (%)	Tensile Elongation at break retention, E _b (%)
Compatible	> 90	80 – 139
Marginal	80 – 89	65 – 79
Not compatible	< 79	< 64 or > 140

This information should be viewed as a screening test. End users are responsible for determining the suitability of these products for their application requirements.

LNP™ ELCRES™ CRX COPOLYMER RESINS

PERFORMANCE PROPERTIES

LNP ELCRES CRX copolymer resins are a new family of polycarbonate copolymers that can provide improved chemical resistance. These resins are based on unique copolymer building block blends offering a combination of:



IMPROVED CHEMICAL RESISTANCE

Improved chemical resistance to a range of chemical disinfectants



IMPACT RETENTION

Retention of ductility upon exposure to chemicals



PROCESSABILITY

Potential for high productivity molding and cycle time reduction



FLAME RETARDANCY

VO rating up to 1.5 mm thickness



AESTHETICS

Consistent opaque color and appearance

POTENTIAL APPLICATIONS - MEDICAL EQUIPMENT HOUSINGS AND ENCLOSURES



Insulin pump



Infusion pump



Dental Chair components



Ultrasound monitor



Hospital Bed components



Surgical Tools



Imaging Devices

PROPERTY PROFILE

Property	Standard	Unit	LNP™ ELCRES™ CRX1414 RESIN	LNP™ ELCRES™ CRX9411 RESIN	LNP™ ELCRES™ CRX5421 RESIN
			Amorphous PC Copolymer	Amorphous PC Copolymer	Semi-crystalline PC copolymer /PBT
Tensile Strength at Yield		MPa	54	52	42
Tensile Strain at Break	ASTM D 638	%	>100	>100	70
Tensile Modulus		MPa	2020	1920	1820
Notched Izod Impact, 23°C	ASTM D 256	J/m	875	765	645
Flame Performance ¹	UL 94 SABIC		HB @ 0.75 mm	VO @ 1.5 mm	HB @ 1.5 mm
MFR, 300 °C, 1.2 kgf	ASTM D 1238	g/10 min	10	10	-
MFR, 250 °C, 5 kgf	ASTM D 1238	g/10 min	-	-	11
Density	ASTM D 792	-	1.2	1.2	1.1
Mold Shrinkage	SABIC method	%	0.6-1.0	0.6-1.0	1.2-1.8

UL yellow card pending¹

CONTACT DETAILS:

Americas

E productinquiries@sabic.com

Technical Answer Center

T +1 800 845 0600

DISCLAIMER: THE MATERIALS, PRODUCTS AND SERVICES OF SAUDI BASIC INDUSTRIES CORPORATION (SABIC) OR ITS SUBSIDIARIES OR AFFILIATES ("SELLER") ARE SOLD SUBJECT TO SELLER'S STANDARD CONDITIONS OF SALE, WHICH ARE AVAILABLE UPON REQUEST. INFORMATION AND RECOMMENDATIONS CONTAINED IN THIS DOCUMENT ARE GIVEN IN GOOD FAITH. HOWEVER, SELLER MAKES NO EXPRESS OR IMPLIED REPRESENTATION, WARRANTY OR GUARANTEE (I) THAT ANY RESULTS DESCRIBED IN THIS DOCUMENT WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (II) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN OR APPLICATION INCORPORATING SELLER'S MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS. UNLESS OTHERWISE PROVIDED IN SELLER'S STANDARD CONDITIONS OF SALE, SELLER SHALL NOT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS, SERVICES OR RECOMMENDATIONS DESCRIBED IN THIS DOCUMENT. Each user is responsible for making its own determination as to the suitability of Seller's materials, products, services or recommendations for the user's particular use through appropriate end-use and other testing and analysis. Nothing in any document or oral statement shall be deemed to alter or waive any provision of Seller's Standard Conditions of Sale or this Disclaimer, unless it is specifically agreed to in a writing signed by Seller. Statements by Seller concerning a possible use of any material, product, service or design do not, are not intended to, and should not be construed to grant any license under any patent or other intellectual property right of Seller or as a recommendation for the use of any material, product, service or design in a manner that infringes any patent or other intellectual property right.

SABIC and brands marked with ™ are trademarks of SABIC or its subsidiaries or affiliates, unless otherwise noted.
© 2020 Saudi Basic Industries Corporation (SABIC). All Rights Reserved.

Any brands, products or services of other companies referenced in this document are the trademarks, service marks and/or trade names of their respective holders.